




# CC7875DT4 EZ RIDER SAW



Tier 4 Final

Powered By:



Blade not included



**20" Blade Capacity**  
**Diesel**

## FEATURES

- Tier 4 Final Deutz® diesel engine
- Fast driving speed out of the cut with 0-300 fpm
- Zero turn radius
- Hydraulically assisted power steering
- 2" double row tapered roller blade shaft bearings
- Vibration isolated adjustable seat and foot rest
- Fully enclosed belt guard keeps belts free of slurry for longer life
- Front wheels are adjustable for green sawing or random crack sawing
- Inboard bearing support for easy belt removal
- Hydrostatic ground drive allows precise speed control
- Blade raise/lower switch is incorporated in joystick for ease of operation
- Three-stage engine air intake filter
- Three lights for night sawing
- Right-side blade mounting only
- Automotive-style sealed front wheel bearings
- Fuel gauge
- Digital read out engine control panel includes tachometer, oil pressure, water temperature and hour meter

**14" & 20" Blade Guards Included**

**CC7875DT4 EZ Rider Saw**



## CC7875DT4 EZ RIDER DIESEL SAW - 74 HP

Model #	Engine Make	Part #	Cat #	Product Weight (lbs.)	Blade Capacity
CC7875DT4	Deutz® Turbo	CC7875DT4	103381	2,540	20"



**Call our Nampa, ID  
Facility at  
800-225-0142  
for more  
information  
and pricing.**

### SPECIFICATIONS

Engine	Deutz TCD 2.2 75HP Tier 4 Final, liquid-cooled, turbo charged, common rail fuel injection system with DOC exhaust aftertreatment maintenance free operation requiring no regeneration diesel, maximum RPM 2600
Blade Shaft	2" diameter
Dimensions	Length: 79", Width: 58", Height: 60", Weight: 2,540 lbs.
Blade Shaft Bearings	2" Double row tapered roller pillow block
Blade Arbor	Industry standard 1" with drive pin
Blade Shaft Drive	3VX540 (10 belts)
Hydraulics	Electric over hydraulic adjustable blade raise/lower. Belt driven hydrostatic ground drive pump.
Electrical	12 Volt electrical system
Travel Speed	0-300 feet per minute
Extra Features	Dual side depth stops, lift frame, water on/off and metering valves, 15 gallon fuel tank, 7 gallon hydraulic tank







# CC8574DD RIDER SAW

## High Productivity in a Ride-On Unit



Tier 4 Final

Powered By:



## 14"-60" Blade Capacity Diesel

Blade not included



### FEATURES

- Redesigned frame for improved rigidity and strength
- Engine and hydraulic cooler work off of the engine-mounted fan
- Coolers located at the rear of the saw to reduce fouling
- Reservoir with clean out access
- Infinitely variable blade speed
- Programmable depth stop
- Updated rear drive motor with increased load capacity, higher top speed, integral parking brake
- Steering actuator for improved control
- Positive neutral lock for wheel drive
- Large diameter front and rear wheels for better traction
- Trailers itself up to a 12 degree incline
- Optional angle arm assembly for angled cutting
- Sauer-Danfoss & Parker blade drive hydraulic components
- Poclain & Parker wheel drive components
- 

**Includes:** Hour Meter, Tachometer, Telescoping Front Pointer, Adjustable Depth Stop, Cup Holder, Quick Disconnect Blade Flanges, Umbrella

### SPECIFICATIONS

Max. Depth of Cut w/ 14" Blade	3-3/4" (6" flange)
Max. Depth of Cut w/ 20" Blade	6-3/4" (6" flange)
Max. Depth of Cut w/ 26" Blade	9-3/4" (6" flange)
Max. Depth of Cut w/ 30" Blade	11-3/4" (6" flange)
Max. Depth of Cut w/ 36" Blade	14-3/4" (6" flange)
Max. Depth of Cut w/ 42" Blade	16-3/4" (7" flange)
Max. Depth of Cut w/ 48" Blade	19-3/4" (8" flange)
Max. Depth of Cut w/ 54" Blade	22-3/4" (9" flange)
Max. Depth of Cut w/ 60" Blade	23-3/4" (10" flange)
Engine Model	Deutz 2.9 Turbo L4 Tier 4 Final
Max. Engine Power	74 HP
Blade Shaft Diameter	2-1/2"
Arbor Size	1" w/single drive pin
Blade Shaft Drive	Hydraulic motor
Blade Mounting	Right side
Blade Raise/Lower	Hydraulic, solenoid valve controlled
Transmission	Variable displacement hydraulic pump & motor
Air Filter	8" Donaldson Alexin
Fuel Capacity	9.5 gallons



## CC8574DD RIDER SAW

Model #	Engine Make	Part #	Cat #	Blade Capacity	Product Weight (lbs.)
CC8574DD-14	Deutz	5803300	78895	14"	3,715
CC8574DD-20	Deutz	5803301	78928	20"	3,725
CC8574DD-26	Deutz	5803302	78949	26"	3,741
CC8574DD-30	Deutz	5803303	78951	30"	3,749
CC8574DD-36	Deutz	5803304	78995	36"	3,763
CC8574DD-42*	Deutz	5803305	78997	42"	3,772
CC8574DD-48*	Deutz	5803306	79001	48"	3,794
CC8574DD-54*	Deutz	5803307	79020	54"	3,870
CC8574DD-60*	Deutz	5803308	79139	60"	3,900

Horsepower and Torque as rated by the engine manufacturer. *\*42" to 60" models include deep cut gearbox.*

## CC8574DD BLADE GUARDS

Description	Part #	Cat #
14" Tapered Mount Blade Guard	6010950	20011
20" Tapered Mount Blade Guard	6010952	08213
26" Tapered Mount Blade Guard	6010954	19322
30" Tapered Mount Blade Guard	6010956	20456
36" Tapered Mount Blade Guard	6010958	13375
42" Tapered Mount Blade Guard	6010960	08216
48" Tapered Mount Blade Guard	6010962	24618
54" Tapered Mount Blade Guard	6010614	99721
60" Tapered Mount Blade Guard	6010616	70666

## CC8574DD OPTIONS

Description	Part #	Cat #
Angle Cutting Arm Assembly Conversion Kit	6040159	22965
Water Pump Kit	6016662	68495
Blade spacing kit-6" flange (for blades 1-1/2" apart)	6010630C	17000
Blade spacing kit-6" flange (for blades 2" apart)	6010631C	21357
Blade spacing kit-6" flange (for blades 4" apart)	6010632C	17592
Large blade gearbox kit 42"	6016682	68496
Large blade gearbox kit 48"	6016683	68499
Large blade gearbox kit 54"	6016684	68500
Large blade gearbox kit 60"	6016685	68554



### Digital User Interface (7"):

- Engine and blade speed
- Engine and hydraulic fluid temperature
- Fuel level
- Hydraulic low level and blade over speed warning



New rear wheel drive bracket for greatly improved strength and reduced hose swing projection. Rear kingpin design with tapered roller bearings in a fully sealed cartridge for greatly improved strength and reliability

### Tight Turning Radius & Integral Parking Brake

Multiple access doors and pivoting hood provide quick access to all filters and hydraulics for ease of maintenance