PRODUCT DATASHEET ICS 695XL POWER CUTTER

695XL Deepest, Most Versatile Gas Power Cutter

The 695XL features include an easy to start engine with higher energy ignition system and durable, long-lasting components including a new muffler, carburetor and piston & cylinder. Available with 12-inch (30 cm), 16-inch (40cm) and 20-inch (50cm) guidebars for the FORCE4 and PowerGrit series diamond chains and 12-inch (30cm), 14-inch (35cm) and 16-inch (40cm) guidebars for the FORCE3 series of diamond chains. Based on the best-selling 695 power cutter platform, the 695XL is the highest horsepower ICS gas power cutter for frequent-use by general construction, utility contractors and concrete professionals.

695XL TECHNICAL SPECIFICATIONS

Bar Cutting Depth	PowerGrit/PowerGrit XL 12in/30cm, 16 in/40cm FORCE3 12in/30cm, 14 in/35cm, 16 in/40cm FORCE4 12 in/30cm, 16 in/40cm
Powerhead Weight	21 lbs/9.6 kg
Engine Speed	9300 +/- 150 rpm (max)
Idling Speed	2700 +/- 100 rpm
Horsepower	6.4 hp (4.8 kW) @ 9000 rpm
Engine Type	2-stroke, single cylinder, air cooled
Displacement	5.7 cu inch (94 cc)
Powerhead Dimensions	18″L x 14″ H x 12″ W (46 cm x 36 cm x 30 cm)
Guaranteed Sound Power Level, Lwa (1)	115 dB(A); (Kwa = 1.0 dB(A))
Sound Pressure Level, at Operator's Ear Lwa (1)	104.6 dB(A): (K = 1.0 dB(A))
Vibration, a hv, eq Concrete Cutting (2)	3.6 m/s² (K=0.2 m/s²) Front Handle 3.1 m/s² (K=0.2 m/s²) Rear Handle
Vibration, a hv, eq Pipe Cutting (2)	5.62 m/s² (K=0.2 m/s²) Front Handle 5.28 m/s² (K=0.2 m/s²) Rear Handle
Water Supply Requirement	Minimum of 20 psi (1.4 bar)
Water Flow Requirement	Minimum: 2 gpm (8 lpm)
Fuel Mix Ratio	50:1 (2%) fuel-to-oil
Fuel Capacity	0.26 gal (1.0 liter)










(1) Measured in accordance with ANSI S12.51-2012/ISO3741:2010 (2) Measured in accordance with ISO5349-1:2001, ISO22867:2011 and ISO19432:2012



ICSDIAMONDTOOLS.COM | 800.321.1240

Effective January 1, 2022 | Copyright 2022 ICS, Oregon Tool Inc. Pricing, product offerings and specifications are subject to change without notice. All rights reserved. ICS, WallWalker, SpeedHook, SeaIPRO, FORCE4, FORCE3 and PowerGrit are registered trademarks of ICS. The best way to cut concrete, DCT, TSS, and ProFORCE are trademarks of ICS. Rev: 112021


PRODUCT DATASHEET ICS 695XL POWER CUTTER



adapter offers easier chain assembly



Deep cutting solution for obstructed or small openings



Easy tensioning of chain



Safer to cut ductile iron



Versatile



ICSDIAMONDTOOLS.COM | 800.321.1240

Effective January 1, 2022 | Copyright 2022 ICS, Oregon Tool Inc. Pricing, product offerings and specifications are subject to change without notice. All rights reserved. ICS, WallWalker, SpeedHook, SeaIPRO, FORCE4, FORCE3 and PowerGrit are registered trademarks of ICS. The best way to cut concrete, DCT, TSS, and ProFORCE are trademarks of ICS. Rev: 112021