

## 890 Series

The ICS 890 Series hydraulic power cutting system offers the superior strength of FORCE4® technology. From the redesigned, more durable rear handle, to the easy to replace drive sprocket, this power cutter is engineered to stand up to your toughest jobs. The flush version cuts within 3/16" of a wall or floor. This package exceeds industry standards and this sleek powerhouse is packed with features designed to make it work as hard as you do.

### 890 SERIES PRODUCT SPECIFICATIONS

	8 gpm (30 lpm)	12 gpm (45 lpm)
Weight w/out bar and chain (1' hose whips)	23.5 lbs (10.6 kg)	
Length	23 inches (58.5 cm)	
Height	10.5 inches (26.5 cm)	
Width	9.5 inches (24 cm)	
Hydraulic Supply	8 gpm (30 lpm) @ 2,500 psi (172.5 bar)	12 gpm (45 lpm) @ 2,500 psi (172.5 bar)
Hydraulic Fluid Requirements (Type)	PC HYDREX MV32 or equivalent	
Water Pressure	Minimum: 20 psi (1.5 bar)	
Water Flow	2 gpm (8 lpm) minimum	
Operating Speed	6,100 rpm (avg. free running) 5,500 sfm (avg. free running chain)	6,500 rpm (avg. free running) 5,800 sfm (avg. free running chain)
Torque*	7.0 ft-lbs (9.6 Nm)	10.0 ft-lbs (13.5 Nm)
Horsepower (1)*	6 hp (4.5 kW)	8 hp (6.0 kW)
Guaranteed Sound Power Level $L_{wa}$ (2)	107 dB(A) (K=0.2 dB(A))	
Equivalent Sound Pressure at the Operator's Ear $L_{pA}$ (2)	98 dB(A) (K=0.7 dB(A))	
Vibration $a_{hv,eq}$ Concrete Cutting (3)	2.0 m/s <sup>2</sup> (K=0.1 m/s <sup>2</sup> ) Front Handle 6.0 m/s <sup>2</sup> (K=1.4 m/s <sup>2</sup> ) Rear Handle	
Vibration $a_{hv,eq}$ PowerGrit Cutting (3)	4.6 m/s <sup>2</sup> (K=0.1 m/s <sup>2</sup> ) Front Handle 4.8 m/s <sup>2</sup> (K=0.3 m/s <sup>2</sup> ) Rear Handle	



- ((1) Measured using 18HP hydraulic power pack (8 gpm/30 lpm and 23HP hydraulic power pack (12 gpm/45 lpm) at 2000psi/138 bar.  
(2) Measured in accordance with ISO3744:2010  
(3) Measured in accordance with ISO5349-1:2001

\* Output ratings based on maximum input conditions and efficiency assumptions and may vary depending on power supply.



Diamond Tools and Equipment

ICSDIAMONDTOOLS.COM | 800.321.1240